



Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066

bondall@bondall.com
www.bondall.com

DURATITE

REVISED: SEPTEMBER 2003

DESCRIPTION

Bondall Duratite is a durable elastomeric membrane, engineered to provide flexibility and increased strength.

Bondall Duratite remains watertight even under permanently wet conditions. The cured membrane is resistant to many chemicals.

Bondall Duratite is suitable for use on shower recesses, tiled areas, basement car park walls, retaining walls and planter boxes. May also be used on stock troughs (metal or concrete), landscape decks, concrete and iron roofs.

This product is not recommended for foot traffic.

TEST AREA. Always test the product on a small inconspicuous area first to ensure the product does not react adversely with surface. Also check if the surface has been previously sealed by carrying out a splash test, by wetting the surface to see if water beads.

FEATURES AND BENEFITS

- Easy to use
- Water based
- Forms a tough, flexible, seamless membrane
- Resistant to algal and fungal growth
- Non toxic
- Environmentally friendly
- Suitable for interior/exterior use

SURFACE PREPARATION

- Surfaces must be sound, clean, dry and free from laitance, dust, oil or grease and any other contaminants. Corroded metal areas should be wire brushed and then pre-treated with a suitable anti-rust coating.
- Concrete must have cured for at least 28 days and be dry before application.
- Ridges and protrusions must be removed prior to application. When repairing areas with small holes and cracks or when joint movement is likely, Bondall Polyweave (a non woven polyester fabric) is recommended for reinforcement.
- Bondall Duratite must be applied to the positive side i.e. to prevent moisture entering the substrate.

APPLICATION

- Note: Do not apply Bondall Duratite if temperature is below 10°C or relative humidity is above 80%. Do not apply if rain is anticipated within 24 hours.
- First coat: Apply at the rate of 1.5m² per litre. If reinforcing is required, whilst coat is still wet work the Polyweave into the Bondall Duratite using a brush or roller. Allow to dry for at least 24 hours.
- Second coat: Apply at 1.5m² per litre at right angles (90°) to the first, ensuring thorough wetting out and coverage of the Polyweave. If the Bondall Polyweave is still exposed after the second coat, apply more Bondall Duratite.
- May be applied by brush, roller or spray.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066
bondall@bondall.com
www.bondall.com

COVERAGE

Approximately 1.5m² per litre per coat. Coverage is a guideline only and may vary considerably due to substrate and application technique.

THINNING

Not required

GLOSS LEVEL

Not applicable

DRYING TIME

Bondall Duratite must be allowed to cure for at least 7 days at 25°C before immersion in water.

CLEAN UP

Clean all equipment promptly with warm water and a little detergent followed by a fresh water rinse immediately after use. Any dried product may be cleaned with mineral turpentine. Do not pour contents or washings down drains or sinks. Dispose as per your local council regulations.

COLOUR

Black

SIZES

1 Litre, 4 Litre & 10 Litre

PRECAUTION/FIRST AID

It is recommended that normal personal protective clothing should be worn, including coveralls, impervious gloves and goggles. Avoid unnecessary skin contact and inhalation. Use a suitable respirator if spray application is employed. If swallowed, contact a doctor or the Poison Information Centre on 13 11 26. Give a glass of water to drink and do not induce vomiting.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066
bondall@bondall.com
www.bondall.com


DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions makes it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Service on 1800 810 123 or (08) 9277 6844



Wholly Australian Owned & Manufactured

the solution  bondall

