



Bondall PTY LTD  
ACN: 008 734 996  
ABN: 27 008 734 996

113 Belmont Ave  
Belmont WA 6104

PO Box 111  
Cloverdale WA 6985

P: 08 9277 8844  
F: 08 9277 4068

bondall@bondall.com  
www.bondall.com

## MONOLAC SLATE DRESSING

REVISED JUNE 2005

### DESCRIPTION

Bondall Monolac is a premium quality single pack, clear dressing for slate, natural stone, unglazed terracotta tiles, quarry tiles, paving bricks and other natural decorative materials. Bondall Monolac is based on a crystal clear acrylic resin.

**TEST AREA.** Always test on a small inconspicuous area, to ensure that the product is achieving the desired result, prior to application over the entire area. Carry out a splash test to check for the porosity of the surface or to test if surface has previously been coated. If water beads do not apply sealer. May not be suitable for some terracotta.

### FEATURES AND BENEFITS

- Enhances the natural colour of stone
- Prevents soiling
- Waterproofs the surface
- Easy to apply
- Suitable for interior and exterior use
- Fast drying
- Hard wearing clear surface

### SURFACE PREPARATION

- Surface preparation is important. All surfaces should be completely dry and free from grease, grime, dust and other contaminants prior to the application of Bondall Monolac. Use Bondall cleaning and preparatory products as required.

### APPLICATION

- Stir well before use, DO NOT SHAKE. Use a 25mm broad timber or metal paddle and stir with a lifting motion to incorporate the entire product.
- Apply Bondall Monolac with a good quality paintbrush, or spray. Treat grout or mortar lines first over an area of 1 to 2 square metres and then fill in as you proceed.
- Apply one coat of Bondall Monolac diluted 1:1 with mineral turps as an initial sealer coat and allow to dry for a minimum of two hours.
- Apply a final coat of Bondall Monolac undiluted to the entire surface.
- No sanding is necessary prior to re-coating. Clean surface and allow to dry and apply another coat of Bondall Monolac when you want to restore the lustre.
- Do not apply if the temperature is below 10°C or if rain is expected within 24 hours.



Wholly Australian Owned & Manufactured

the solution **is** bondall





Bondall PTY LTD  
ACN: 008 734 996  
ABN: 27 008 734 996

113 Belmont Ave  
Belmont WA 6104

PO Box 111  
Cloverdale WA 6985

P: 08 9277 8844  
F: 08 9277 4068

bondall@bondall.com  
www.bondall.com

## COVERAGE

Approximately 10 square metres per litre on high -density surfaces and 4-5 square metres on highly porous surfaces.

## THINNING

Thin first coat only 1:1 with mineral turps.

## GLOSS LEVEL

Not applicable.

## DRYING TIME

Bondall Monolac will be touch-dry in 2 hours. Drying times are a guide only. Longer drying times may be required in cooler or humid conditions. Allow drying for as long as possible before full use, light foot traffic is permissible after 4-6 hours depending on the weather conditions at the time. Allow at least 24 hours before allowing heavy traffic.

## CLEAN UP

Clean all equipment promptly with mineral turps followed by a warm water rinse with a little detergent added. Do not pour contents or washing down drains or sinks. Dispose of as per your council regulations.

## COLOUR

Clear.

## SIZES

Available in 1 litre, 4 litre and 20 litre containers.



Wholly Australian Owned & Manufactured

the solution **is** bondall





Bondall PTY LTD  
ACN: 008 734 996  
ABN: 27 008 734 996

113 Belmont Ave  
Belmont WA 6104

PO Box 111  
Cloverdale WA 6985

P: 08 9277 6844  
F: 08 9277 4068

bondall@bondall.com  
www.bondall.com

## PRECAUTION/FIRST AID

It is recommended that normal personal protective clothing should be worn, including coveralls, impervious gloves and goggles. Avoid unnecessary skin contact and inhalation. Flammable – Keep away from naked flame.

If swallowed, contact a doctor or the Poison Information Centre on 13 11 26. Give water to drink and do not induce vomiting.

## DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions makes it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Service on 1800 810 123 or (08) 9277 6844



Wholly Australian Owned & Manufactured

the solution **is** bondall

