



Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066
bondall@bondall.com
www.bondall.com

POLBOND 7000

AM0003

☒

REVISED JAN 2002

DESCRIPTION

Bondall Polbond 7000 is a versatile and heavy-duty woodworking PVA adhesive combining a quick setting time with a medium open time. It is non-staining; non-irritant to the skin, non-damaging to cutting tools, does not soften under sanding and is a moisture and humidity resistant.

Bondall Polbond 7000 has a negligible tendency to run on vertical surfaces and exhibits very good wet tack for block gluing as well as being for dowel and tenon gluing, rabbet and finger joining.

High quality PVA woodworking adhesive designed for fast drying and bonds of high tensile strength. It is particularly suitable for door manufacturing, sands freely and does not clog sanding belts. It has good water resistance.

FEATURES AND BENEFITS

- Versatile
- Easy to use
- Dries very hard
- Extremely strong
- Good water resistance
- Quick-setting
- Non-staining
- Non-toxic
- Moisture and humidity resistant

SURFACE PREPARATION

Ensure surface is dirt and grease free. Apply direct from container to one surface only. Press surfaces together and lightly clamp. Wipe excess adhesive away with a cloth. Bondall Polbond 7000 sets in approximately 30 minutes. Maximum strength is achieved in 24 hours

APPLICATION

By hand, glue gun or squeeze bottle.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066
bondall@bondall.com
www.bondall.com

COVERAGE

Not applicable

THINNING

Unnecessary. If essential then dilute with water.

GLOSS LEVEL

Not applicable.

DRYING TIME

Bondall Polbond 7000 sets in approximately 30 minutes. Maximum strength is achieved in about 24 hours

CLEAN UP

DO NOT POUR CONTENTS OR WASHING DOWN DRAINS OR SINKS.

Clean equipment in running water.

COLOUR

White liquid, dries clear

SIZES

20L pails and 200L drums. Larger upon request.

PRECAUTION/FIRST AID

It is recommended that normal personal protective clothing should be worn, including coveralls, impervious gloves and goggles. Avoid unnecessary skin contact and inhalation – use a suitable respirator if spray application is employed.

If swallowed, contact a doctor or the Poison Information Centre on 13 11 26. Give water to drink and do not induce vomiting.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066
bondall@bondall.com
www.bondall.com

DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions makes it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Service on 1800 810 123 or (08) 9277 6844



Wholly Australian Owned & Manufactured

the solution  bondall

