



Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066

bondall@bondall.com
www.bondall.com

RIDGE POINTING COMPOUND

REVISED: SEPTEMBER 2003

DESCRIPTION

Bondall Ridge Pointing Compound is a highly flexible pointing compound with excellent adhesion properties. It will provide long term durability under harsh Australian conditions. Bondall Ridge Pointing Compound is suitable for use with new and old ridge capping.

FEATURES AND BENEFITS

- Ready to use
- Excellent adhesion
- Good flexibility
- Good water resistance
- Easy trowel application
- Trowels to a smooth finish
- Durable

SURFACE PREPARATION

- Surface must be clean, dry, and free of dust and other contaminants and be in a sound condition.
- Re-bed capping where necessary with sand/cement mortar using Bondall Bondcrete admixture in the gauging water.

APPLICATION

- Lubricate trowel with water.
- To "wet up" Bondall Ridge Pointing Compound do NOT add water; simply agitate Bondall Ridge Pointing Compound with the trowel.
- Apply to a thickness of 3mm to 5 mm. Greater thickness increases drying time and sagging.
- Point approximately 1 meter of ridge capping at a time and trowel to a smooth finish.
- Weep holes should be built in before curing has progressed too far.

COVERAGE

Approximately 2.5m² per litre.

4-5 ridge caps/per litre

THINNING

Not recommended



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066
bondall@bondall.com
www.bondall.com

DRYING TIME

At temperature of 25° and at 50% humidity Bondall Ridge Pointing Compound is water resistant after 2 hours. Allow a longer curing time for low temperatures and high humidity conditions.

CLEAN UP

Do not pour contents or washings down drains or sinks. Clean all equipment with warm water before product dries. Dispose of as per your local council regulations.

COLOUR

Terra cotta, charcoal, red earth and paintable grey

SIZES

4 litre and 10 litre

PRECAUTION/FIRST AID

It is recommended that normal personal protective clothing should be worn, including coveralls, impervious gloves and goggles. Avoid unnecessary skin contact and inhalation – use a suitable respirator if spray application is employed. If swallowed, contact a doctor or the Poison Information Centre on 13 11 26. Give a glass of water to drink and do not induce vomiting. A Material Safety Data Sheet is available on request.

DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions make it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Service on 1800 810 123 or (08) 9277 6844



Wholly Australian Owned & Manufactured

the solution  bondall

