



Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066

bondall@bondall.com
www.bondall.com

TERRATITE

REVISED: SEPTEMBER 2006

DESCRIPTION

Bondall TerraTite is a user friendly brushable waterproofing system in a terra-cotta colour. The finish forms a flexible, yet tough, seamless membrane for permanent immersion in water. Bondall TerraTite is environmentally friendly, simple to use and can be easily washed and cleaned. Bondall TerraTite accommodates moderate surface cracking and has good UV and weather resistant qualities

For questions regarding the suitability of TerraTite for your intended surface, please contact Bondall's Advisory Service on 1800 810 123 or (08) 9277 6844, or visit the Bondall website www.bondall.com

AREAS OF USE

* Ideal for waterproofing:

- Terra-cotta pots
- Planter boxes
- Pottery
- Bird baths
- Fish ponds (Refer to PondTite data sheet)
- Water features
- Reflecting pools

* also designed to:

- Repair terra-cotta or masonry ornaments and provide a decorative finish
- Change the appearance of masonry surfaces

X Not intended for:

- Swimming pools & Spas
- Glass or fiberglass
- Glazed or semi-glazed surfaces
- Plastic, metal or wood
- Use with other 'Tite' Membranes
- On non-porous surfaces



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066

bondall@bondall.com
www.bondall.com

SURFACE PREPARATION

- For application instructions for use in a pond/water feature, please refer to the PondTite Waterproofing Pond Sealer label or data sheet available on the Bondall website www.bondall.com
- Ensure surface is structurally sound. Remove any previous coatings right back to the original layer. Surface should be free from dirt, dust, salts, grease, oil or other contaminants.
- Do not apply if temperature is below 10°C, if humidity is high or rain is expected.
- If renewable moisture is present or if in doubt of surface condition or adhesions Bondall Epoxy Prep Surface Conditioner or a 5-10mm cement render (with Bondall Hydrocrete incorporated should be applied and allowed to cure prior to applying TerraTite.
- Ensure surface is dry; fill any holes or cracks up to 3mm in width with TerraTite.
- When applying to larger cracks, corners or expansion joints use reinforcing fabric (PolyWeave). Embed into a generous 150mm-wide coat applied adjacent to and across the tape then apply a further fully saturated coat and allow to dry. Apply one additional coat to ensure fabric is thoroughly covered without pinholes.
- For small repairs, apply a generous coat to both edges of the broken piece and join together. Wipe off excess, allow setting for 2 hours then applying reinforcing fabric (PolyWeave) to the repaired surface and continue as above.
- Prime soft, highly porous or easily crushed surface (eg limestone or sandstone) with TerraTite diluted with 10% water. Allow 48 hours drying time before following Application procedure.

APPLICATION

- Carefully follow "Surface Preparation" instructions
- For application instructions for use in ponds/water features, please refer to the PondTite Waterproofing Pond Sealer label or data sheet available on the Bondall website www.bondall.com
- Stir Bondall TerraTite slowly with a broad blade or paddle to avoid aeration. Do not shake can.
- Apply directly from can as dilution is generally not necessary but in warm conditions. To aid application dilute by no more than 1-2% using clean water or use a water spray to cool the surface and allow to dry.
- Half load the brush to give a smoother finish and complete small areas at a time. A minimum thickness of 0.6mm (dry finish 2 coats is recommended) is recommended.
- Apply first coat and allow overnight drying or longer if conditions are cold, damp or humid. Do not exceed 72 hours before application of second coat.
- Apply second coat at right angles to first coat.
- Allow at least 7 full days drying time before allowing water/moisture to come in contact with the coating.

COVERAGE

Do not exceed 1.5m² per Litre per coat on smooth surfaces. Calculate area carefully as using insufficient product will lead to failure.

THINNING

Not recommended



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066
bondall@bondall.com
www.bondall.com

GLOSS LEVEL

Not applicable.

CLEAN UP

- Reseal container of unused TerraTite immediately after use.
- Clean all equipment promptly with soapy water and a stiff bristled brush.
- Use methylated spirits if product has dried or hardened.
- Rinse thoroughly with fresh water.
- Please dispose of any waste responsibly.
- Do not pour TerraTite or washings down drains or sinks.

COLOUR

Terra-cotta

SIZES

500ml 1 Litre and 4 Litre

PRECAUTION/FIRST AID

- Avoid contact with eyes or skin.
- Wear protective gloves, clothing and eyewear (recommended).
- Seal container when not in use.
- Keep out of reach of children.
- If accidental poisoning occurs, seek urgent medical advice or contact the Poison Information Centre on 131126.

MSDS available on request.

This data sheet supersedes all other printed material.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066
bondall@bondall.com
www.bondall.com

DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions makes it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Service on 1800 810 123 or (08) 9277 6844



Wholly Australian Owned & Manufactured

the solution  bondall

