



Bondall PTY LTD
ACN: 008 734 996
ABN: 27 008 734 996

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4068

bondall@bondall.com
www.bondall.com

WAPOL ACRYLIC ROOF GLAZE

REVISED: JUNE 2006

DESCRIPTION

Bondall Wapol Roof Glaze is a hard-wearing, 100% acrylic clear finish specially designed for high quality exterior applications. Bondall Wapol Roof Glaze is formulated using a thermoplastic all acrylic water-resistant binder that is resilient to weather with added UV resistance. Use Bondall Wapol Roof Glaze to enhance the appearance of old or newly painted tiles and to reglaze terra cotta tiles.

SURFACE PREPARATION

- Surface preparation is critical and must be strictly observed. Surfaces must be free from grease, grime, dust, dirt, moss, lichen, loose and flaking paint and surface oxidation.
- If the roof is used for the collection of rainwater disconnect the pipe to the storage unit before preparation begins and leave disconnected until after the first substantial rainfall following the application of the Bondall CFA Roof Coat System.
- Replace any cracked or broken tiles and re-bed ridge caps if necessary and re-point the ridge caps with Bondall Ridge Pointing Compound.
- Clean the roof with a high-pressure water cleaner working from the ridge down to remove all moss, lichen or other contaminants.
- If moss or mould is present it should be treated with Bondall Wapol FW5 Fungicide Wash.

APPLICATION

Terra Cotta or aged concrete tiles

- Stir well before use.
- Apply 1st coat of Bondall Wapol Roof Glaze diluted 50:50 with clean water by airless spray and allow to dry for a minimum of 4 hours. Apply the 2nd coat of Bondall Wapol Roof Glaze undiluted and allow to dry.

Painted Surfaces

- Stir well before use.
- Apply one coat of Bondall Wapol Roof Glaze undiluted by airless spray and allow to dry.

IMPORTANT NOTES!

- Bondall Wapol Roof Glaze is a maintenance coating and will require re-coating in the future to ensure the integrity of the system.
- As some terra cotta tiles are extremely hard and dense a water spot test should be undertaken on several areas of the roof to ensure the tiles will accept the roof glaze prior to application.



Wholly Australian Owned & Manufactured

the solution  bondall



Quality
Endorsed
Company
ISO 9002 L: 2108
Sydney Australia



Bondall PTY LTD
ACN: 008 734 996
ABN: 27 008 734 996

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4068

bondall@bondall.com
www.bondall.com

COVERAGE

Bondall Wapol Roof Glaze will cover approximately 8²m per litre depending on the type of roof, porosity of substrate, tip size used and application technique.

THINNING

Not normally required other than for the first coat for terra cotta tiles.

GLOSS LEVEL

65-75% on 60° gloss meter.

DRYING TIME

Bondall Wapol Roof Glaze is touch dry in approximately 30 minutes and can be re-coated after 4 hours. Drying times are a guide only and longer drying times may be required under cool or humid conditions. Do not apply Bondall Wapol Roof Glaze if the temperature is below 10°C or if rain is expected within 24 hours or whitening may occur.

COLOUR

White liquid, clear when dry

CLEAN UP

Clean equipment promptly in warm water and a little detergent added followed by a fresh water rinse.
Do not dispose of into open waterways or drains. Dispose of as per your local council regulations.

SIZES

20 litre containers.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 996
ABN: 27 008 734 996

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4068

bondall@bondall.com
www.bondall.com

PRECAUTION/FIRST AID

SAFETY/FIRST AID

- It is recommended that normal protective clothing should be worn, including coveralls, impervious gloves and goggles.
- Avoid unnecessary skin contact and inhalation – use a suitable respirator if spray application is employed.
- If poisoning occurs give a glass of water to drink and contact the Poisons Information Centre on 13 11 26.

Refer to MSDS for more details

This data sheet supersedes all previous printed material

DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions makes it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Advisory Service on 1800 810 123 or (08) 9277 6844 or visit www.bondall.com



Wholly Australian Owned & Manufactured

the solution  bondall

