

Material Safety Data Sheet

CS: 1.4.92

Page: 1 of 5

Infosafe No™ HXR5Y Issue Date : December 2009 ISSUED by BONDALL

Product Name **POOL PAVING SEALER**

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name POOL PAVING SEALER
Product Code 94123, 94125, 94126
Company Name BONDALL PTY LTD (ABN 27 008 734 996)
Address 113 Belmont Avenue
Belmont
WA 6104 Australia
Emergency Tel. 0400 705 773 or Poisons Information Centre: 13 11 26
Telephone/Fax Number Tel: (08) 6272 3800
Fax: (08) 9277 4068
Recommended Use Waterproofing surface treatment.

2. HAZARDS IDENTIFICATION

Hazard Classification HAZARDOUS SUBSTANCE.
DANGEROUS GOODS.
Hazard classification according to the criteria of NOHSC.
Dangerous goods classification according to the Australia Dangerous Goods Code.

Risk Phrase(s) R10 Flammable.
R38 Irritating to skin.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 Harmful: may cause lung damage if swallowed.

Safety Phrase(s) S23 Do not breathe gas/fumes/vapour/spray
S24/25 Avoid contact with skin and eyes.
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
S38 If insufficient ventilation, wear suitable respiratory equipment.
S61 Avoid release to the environment. Refer to special instructions/safety data sheet.
S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Name	CAS	Proportion
	White Spirit	64742-88-7	>60 %
	Distillates (petroleum), hydrotreated light Ingredients	64742-47-8	<10 %
	determined not to be hazardous		Balance

4. FIRST AID MEASURES

Inhalation If inhaled, remove from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

Ingestion If swallowed, do NOT induce vomiting. Wash mouth thoroughly with water. Seek immediate medical attention.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Ensure contaminated clothing is washed before re-use or discard. If irritation develops seek medical attention.

Eye If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing for several minutes until all contaminants are washed off completely. Seek medical attention.

First Aid Facilities Eye wash station, safety shower and normal washroom facilities.

Advice to Doctor Treat symptomatically.

Other Information For advice in an emergency, contact a Poisons Information Centre (Phone Australia 13 11 26) or a doctor at once.

Material Safety Data Sheet

CS: 1.4.92

Page: 2 of 5

Infosafe No™ HXR5Y

Issue Date : December 2009

ISSUED by BONDALL

Product Name **POOL PAVING SEALER**

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media	Foam, water fog, water spray, carbon dioxide or dry chemical powder.
Hazards from Combustion	Under fire conditions the product may emit toxic fumes including carbon monoxide and carbon dioxide.
Products Specific Hazards	Flammable liquid. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create a fire hazard. Heating can cause expansion or decomposition leading to violent rupture of containers. 3[Y]
Hazchem Code	
Precautions in connection with Fire	Fire-fighters should wear full protective clothing and self contained breathing apparatus (SCBA) operated in positive pressure mode. Use water spray to cool storage containers and tanks, pipelines and fire-exposed surfaces.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures	Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water authorities and EPA in accordance with local regulations.
-----------------------------	---

7. HANDLING AND STORAGE

Precautions for Safe Handling	Wear appropriate protective clothing and equipment to prevent inhalation, skin and eye contact. Handle and use the material in a well-ventilated area, away from sparks, flames and other ignition sources. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Work from suitable, labelled, fire-resistant containers. Keep containers closed when not in use. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Maintain a high level of personal hygiene when using the product, that is, always wash hands after handling, and before eating, drinking, smoking or using the toilet facilities.
Conditions for Safe Storage	Store in a cool, dry, well ventilated area away from sources of ignition, oxidising agents, foodstuffs and out of direct sunlight. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all Local, State and Federal regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

National Exposure Standards	No exposure standards have been established for this material by the National Occupational Health & Safety Commission (NOHSC), Australia. However, the available exposure standards for ingredients are stated below:
------------------------------------	---

National Occupational Health And Safety Commission (NOHSC), Australia Exposure Standards:

Substance	TWA		STEL		NOTICES
	ppm	mg/m ³	ppm	mg/m ³	
White spirit	-	790	-	-	-

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Material Safety Data Sheet

CS: 1.4.92

Page: 3 of 5

Infosafe No™ HXR5Y	Issue Date : December 2009	ISSUED by BONDALL
--------------------	----------------------------	-------------------

Product Name **POOL PAVING SEALER**

Biological Limit Values	No biological limit allocated.
Engineering Controls	Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof local exhaust ventilation system is required.
Respiratory Protection	If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapour filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.
Eye Protection	Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.
Hand Protection	Wear laminated film, nitrile or other suitable gloves conforming to AS/NZS 2161: Occupational protective gloves.
Body Protection	Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist. Industrial clothing should conform to the specifications detailed in AS/NZS 2919: Industrial clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear liquid.
Odour	Hydrocarbon solvent odour.
Melting Point	Not available
Boiling Point	180°C approx.
Solubility in Water	Insoluble
Specific Gravity	0.900
Vapour Pressure	2 mmHg at 25°C
Vapour Density (Air=1)	>1
Evaporation Rate	<1 (n-Butyl acetate=1)
Volatile Component	90%
Flash Point	50°C (SETA)
Flammability	Flammable liquid.
Auto-Ignition Temperature	Not available
Flammable Limits - Lower	0.60%
Flammable Limits - Upper	Not available

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under normal conditions of storage and handling.
Incompatible Materials	Strong oxidising agents.
Hazardous Decomposition Products	Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon monoxide and carbon dioxide.
Hazardous Polymerization	Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information	No toxicity data are available for this specific product.
-------------------------------	---

Material Safety Data Sheet

CS: 1.4.92

Page: 4 of 5

Infosafe No™ HXR5Y	Issue Date : December 2009	ISSUED by BONDALL
--------------------	----------------------------	-------------------

Product Name **POOL PAVING SEALER**

Inhalation	Vapours may cause drowsiness and dizziness. High vapour concentrations are irritating to the respiratory tract and may cause central nervous system depression.
Ingestion	Harmful: may cause lung damage if swallowed. Ingestion may cause nausea, vomiting and CNS depression with symptoms including drowsiness, dizziness, weakness, fatigue, headache, confusion and possible unconsciousness. Subsequent to ingestion or vomiting, small amounts of liquid aspirated into the respiratory system may cause severe pulmonary injury that may lead to death.
Skin	Irritating to skin. Symptoms may include redness and itchiness. Repeated exposure may cause skin dryness and cracking, and may lead to dermatitis.
Eye	May cause irritation to eyes. Symptoms may include redness, tearing, stinging and swelling.
Chronic Effects	Prolonged or repeated skin contact may cause defatting leading to dermatitis. Prolonged or repeated exposure may also damage the blood organs, lungs, liver, kidneys and nervous system.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Persistence / Degradability	Not available
Mobility	Not available
Bioaccumulative Potential	Not available
Environ. Protection	Avoid contaminating waterways. Do not discharge the product into drains or sewers.

13. DISPOSAL CONSIDERATIONS

Disposal Considerations	The disposal of the spilled or waste material must be done in accordance with applicable local and national regulations.
--------------------------------	--

14. TRANSPORT INFORMATION

Transport Information	This material is a Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. Class 3 - Flammable Liquids are incompatible in a placard load with any of the following: - Class 1, Explosives - Class 2.1, Flammable Gases, if both the Class 3 and Class 2.1 dangerous goods are in bulk - Class 2.3, Toxic Gases - Class 4.2 Spontaneously Combustible Substances - Class 5.1 Oxidising Agents and Class 5.2, Organic Peroxides - Class 6 Toxic Substances (where the flammable liquid is nitromethane) - Class 7 Radioactive Substances.
U.N. Number	1263
Proper Shipping Name	PAINT
DG Class	3
Hazchem Code	3[Y]
Packaging Method	3.8.3RT1
Packing Group	III
EPG Number	3C1
IERG Number	14

15. REGULATORY INFORMATION

Regulatory Information	Classified as Hazardous according to criteria of National Occupational Health & Safety Commission (NOHSC), Australia. Classified as a Scheduled Poison S5 according to the Standard for the Uniform
-------------------------------	--

Material Safety Data Sheet

CS: 1.4.92

Page: 5 of 5

Infosafe No™ HXR5Y	Issue Date : December 2009	ISSUED by BONDALL
--------------------	----------------------------	-------------------

Product Name **POOL PAVING SEALER**

Poisons Schedule	Scheduling of Drugs and Poisons (SUSDP). S5
Hazard Category	Harmful, Irritant, Dangerous for the environment
AICS (Australia)	All components of this product are listed on the Australian Inventory of Chemical Substances (AICS).

16. OTHER INFORMATION

Date of preparation or last revision of MSDS	MSDS Reviewed: December 2009 Supersedes: May 2006
Contact Person/Point	Chemist: Tel No: (08) 9478 6005 Emergency: Tel No: 0400 705 773 ...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd. The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.