



Bondall PTY LTD
ACN: 008 734 996
ABN: 27 008 734 996

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 8844
F: 08 9277 4068

bondall@bondall.com
www.bondall.com

AQUATITE

REVISION DATE: SEPTEMBER 2007

DESCRIPTION

Bondall AquaTite is a grey, brushable, waterproofing coating that forms a flexible yet tough, seamless membrane. This single pack product exceeds the Australian quality standards (3740-1994). It accommodates moderate surface cracking and is resistant to algal and fungal growth. It also can be sanded to a smooth finish for application of water-based paints or other protective coatings. It should not be used as a finishing coat or top coat.

For questions regarding the suitability of AquaTite for your intended surface area, please contact Bondall Advisory Service on 1800 810 123 or (08) 9277 6844, or visit the Bondall website www.bondall.com

AREAS OF USE

AREAS OF USE

√ Ideal for:

- Shower recess, bathrooms, laundry & kitchen wet areas
- Cured concrete slabs & decks on terraces & balconies prior to tiling
- Planter boxes, unglazed terracotta pots, non-potable water tanks & fish ponds
- Roofs & retaining walls
- Joint-free surfaces such as fibre-cement, compressed sheeting, plasterboard, brick and most suitably primed metal surfaces
- Holding tanks (non potable)
- Fish ponds

Also designed as:

- Crack/gap filler for masonry and unglazed ceramics
- Sealants against leaks
- Repairer for roof cracks and gutters

X Not intended for:

- Uncured concrete (allow a minimum of 4 weeks curing or apply Epoxy Prep Surface Conditioner)
- Concrete surfaces treated with other sealants or waterproofers (e.g. BondCrete, Silasec)
- Swimming pools, spas
- Glass, fiberglass, glazed or semi-glazed surfaces, plastic, wood
- Painted surfaces, plastic or rubber type surfaces
- Underneath other "Tite" range of products
- Surfaces experiencing renewable moisture



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 996
ABN: 27 008 734 996

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4068

bondall@bondall.com
www.bondall.com

SURFACE PREPARATION

- Ensure surface is structurally sound. Remove any previous coatings right back to the original surface layer. Surface should be free from dirt, dust, salts, grease, oil or other contaminants.
- If renewable moisture is present or if in doubt of surface condition or adhesion, Bondall Epoxy Prep Surface Conditioner is required.
- Fill any holes or cracks with a fine sand/cement mortar (Bondall Hydrocrete recommended), thoroughly worked into the area.
- When applying to larger cracks, corners or expansion joints use 100mm reinforcing fabric (Polyweave). Embed into and apply a generous 150mm-wide coat adjacent to and across the tape, then apply a further fully saturated coat and allow to dry. Apply one additional coat to ensure fabric is thoroughly covered without pinholes.
- Prime soft, highly porous or easily crushed surfaces (e.g. natural limestone) with AquaTite mixed with 10% water. Allow 48 hours drying time.
- If uncertain of surface preparation requirements, surface conditions or surface suitability of product, please refer to special instructions on Bondall's website www.bondall.com or contact the Bondall Advisory Service on Toll Free 1800 810 123 or (08) 9277 6844.

APPLICATION

- Do not apply if temperature is below 10 C, if humidity is high or if rain is expected.
- Stir AquaTite slowly with a broad blade or paddle. Do not shake can.
- Using a medium to firm bristle, quality paint brush, apply directly from can as dilution is generally not necessary. In hot conditions, use water spray to cool surface (preferred) and allow to dry or dilute AquaTite by no more than 1-2% using clean water.
- Half load the brush to give a smoother finish and complete small areas at a time. A minimum film thickness of 0.6mm (dry finish) is recommended.
- Apply 2 coats (minimum) for waterproofing. Water resistance increases with the amount of coats. If pinholes or flaws appear in first coat, apply a further 2 coats.
- Allow overnight drying or longer if conditions are cold, damp or humid. Do not exceed 72 hours before application of second coat.
- Apply second coat at right angles to first coat.
- Allow 24 hours curing before using a flexible, rubber cement or water based tile adhesive as per manufacturer's instructions.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 996
ABN: 27 008 734 996

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 8844
F: 08 9277 4068

bondall@bondall.com
www.bondall.com

SURFACE PREPARATION - FOR USE WITH WATER FEATURES AND PONDS

- Ensure surface is structurally sound. Remove any previous coatings right back to the original layer. Surface should be free from dirt, dust, salts, grease, oil or other contaminants.
- Do not apply if temperature is below 10 C, if humidity is high or if rain is expected.
- Carefully prepare the surface. (For a list of unsuitable surfaces, please refer to the special instructions on the Bondall website).
- Ensure surface is free from any sharp edges or 'dags'.
- If renewable moisture is present or if in doubt of surface condition or adhesion, Bondall Epoxy Prep Surface Conditioner is required.
- Fill any holes or cracks with a fine sand/cement mortar (Bondall Hydrocrete recommended), thoroughly worked into the area.
- Clean thoroughly to ensure surface is free from dirt, dust, salts, grease, oil or other contaminants.
- If uncertain of surface preparation requirements, surface conditions or suitability of product, please refer to special instructions on Bondall's website www.bondall.com or contact the Bondall Advisory Service on Toll Free 1800 810 123 or (08) 6272 3800.

APPLICATION - FOR USE WITH WATER FEATURES AND PONDS

- Stir AquaTite slowly with a broad blade or paddle. Do not shake can.
- Use a medium to firm-bristle, quality paint brush.
- Apply directly from the can as dilution is generally not necessary but in warm conditions, to aid application dilute by no more than 5% using clean water.
- Apply a substantially thicker coating than paint, avoiding excess build-up in corners. Ensuring no bubbles are left.
- Apply first coat and allow overnight drying or longer if conditions are cold, damp or humid. Do not exceed 72 hours before application of second coat.
- Apply second coat at right angles to first coat.
- If covering pond allow sufficient air flow while drying.

APPLICATION - FILLING THE POND

- Allow at least 7 full days drying time before allowing water to come in contact with the coating. Allow longer drying times in cold, damp or humid conditions.
- After 7 full days drying mix a small amount of dishwashing liquid with clean water in a bucket and sponge surface with soapy water to remove any PondTite residue.
- Rinse pond thoroughly with fresh, clean water, removing all traces of the detergent.
- Fill pond with clean water and leave for 1 - 2 days.
- Empty pond and refill with clean water again.
- Before adding fish or plants, carefully follow water conditioning instructions from fish or aquaculture suppliers.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 996
ABN: 27 008 734 996

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 8844
F: 08 9277 4068

bondall@bondall.com
www.bondall.com

COVERAGE

Do not exceed 1.5m² per Litre per coat on smooth surfaces.

THINNING

Not recommended

GLOSS LEVEL

Not applicable.

DRYING TIME

- Allow overnight drying or longer if conditions are cold, damp or humid. Do not exceed 72 hours before application of second coat.
- Allow 24 hours curing before using a flexible, rubber cement or water based tile adhesive as per manufacturer's instructions.

CLEAN UP

- Clean all equipment promptly with soapy water and a stiff bristle or wire brush.
- Use methylated spirits if product has dried or hardened.
- Rinse thoroughly with fresh water.
- Please dispose of any waste materials responsibly.

COLOUR

Grey

SIZES

1 Litre 4 Litre and 10 Litre



Wholly Australian Owned & Manufactured

the solution **is** bondall





Bondall PTY LTD
ACN: 008 734 996
ABN: 27 008 734 996

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4068

bondall@bondall.com
www.bondall.com

PRECAUTION/FIRST AID

- Avoid contact with eyes or skin.
- Wear protective gloves, clothing and eyewear (recommended).
- Seal container when not in use.
- Keep out of reach of children.
- If accidental poisoning occurs, seek urgent medical advice or contact the Poison Information Centre on 13 11 26.
- Material Safety Data Sheet available on request.

DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions makes it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Service on 1800 810 123 or (08) 9277 6844



Wholly Australian Owned & Manufactured

the solution **is** bondall

