

SAFETY DATA SHEET

BETTA UNDER TILE MEMBRANE

Infosafe No.: LQ7JJ
Issued Date: 27/01/2017
Issued by: BONDALL PTY LTD

1. IDENTIFICATION

GHS Product Identifier

BETTA UNDER TILE MEMBRANE

Company Name

BONDALL PTY LTD (ABN 27 008 734 996)

Address

113 Belmont Avenue Belmont
WA 6104 Australia

Telephone/Fax Number

Tel: Australia: +61 (8)6272 3800 / New Zealand: 0800 474 7738

Fax: +61 (8)9277 4068

Emergency phone number

+ 61400 705 773 or Poisons Information Centre: 0800 764 766

Recommended use of the chemical and restrictions on use

Waterproof membrane.

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture

Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.
Not classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433:2012 Transport of Dangerous Goods on Land.

6.7B Substance that is a suspected human carcinogen

6.8B Substance that is suspected to be a human reproductive or developmental toxicant

Signal Word (s)

WARNING

Hazard Statement (s)

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

Pictogram (s)

Health hazard

**Precautionary statement – Prevention**

P103 Read label before use.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P281 Use personal protective equipment as required.

Precautionary statement – Response

P308+P313 IF exposed or concerned: Get medical advice/attention.

Precautionary statement – Storage

P405 Store locked up.

Precautionary statement – Disposal

P501 In the case of a substance that is in compliance with a HSNO approval other than a Part 6A (Group Standards) approval, a label must provide a description of one or more appropriate and achievable methods for the disposal of a substance in accordance with the Hazardous Substances (Disposal) Regulations 2001. This may also include any method of disposal that must be avoided. See Section 13 for disposal details.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients

Name	CAS	Proportion
Styrene	100-42-5	0.1-1 %
Ingredients determined to be non-hazardous		Balance

4. FIRST-AID MEASURES

Inhalation

If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention..

Ingestion

Do not induce vomiting. Wash out mouth thoroughly with water. Seek medical attention.

Skin

Wash affected area thoroughly with soap and water. If symptoms develop seek medical attention.

Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. If symptoms develop, seek medical attention.

First Aid Facilities

Eyewash and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre or a doctor at once. (0800 764 766)

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray, water fog, foam, carbon dioxide and dry chemical powder.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide and carbon dioxide as well as trace amounts of vinyl acetate monomers, oxides of sulphur and oxides of nitrogen.

Specific Hazards Arising From The Chemical

This product is not combustible. However, under fire conditions, following the evaporation of the aqueous component, the organic components may decompose and/or burn.

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. Fight fire from safe location.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Slippery when spilled. Avoid accidents, clean up immediately. Wear appropriate personal protective equipment and clothing to prevent exposure. Increase ventilation. If possible contain the spill. Place inert absorbent material onto spillage. Collect the material and place into a suitable labelled container. Do not dilute material but contain. As a water based product, if spilt on electrical equipment the product will cause short-circuits. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid inhalation of vapours and mists, and skin or eye contact. Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Maintain high standards of personal hygiene i.e. Washing hands prior to eating, drinking, smoking or using toilet facilities. Avoid exposure. Do not handle until all safety precautions have been read and understood. It is recommended that pregnant or breastfeeding women should not handle this product unless adequate exposure protection can be assured at all times. Female personnel planning pregnancy should be made aware of the potential risks.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area, out of direct sunlight. Store in suitable, labelled containers. Keep containers tightly closed. Store away from incompatible materials. Ensure that storage conditions comply with applicable local and national regulations. Protect from freezing.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limit values

No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

Styrene

TWA: 50 ppm

TWA: 213 mg/m³

STEL: 100 ppm

STEL: 426 mg/m³

Notices: 6.7A (Skin)

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

'Sk' Notice: Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

6.7A: Confirmed carcinogen

Biological Limit Values

Name: Styrene

Determinant: Mandelic acid plus phenylglyoxylic acid in urine

Value: 400 mg/g creatinine

Sampling time: end of shift.

Name: Styrene

Determinant: Styrene in urine

Value: 40 µg/L

Sampling time: end of shift.

Source: American Conference of Industrial Hygienists (ACGIH)

Appropriate Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material such as Neoprene/rubber gloves. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Description	Properties	Description
Form	Liquid	Appearance	Sky blue thixotropic liquid/paste
Colour	Sky blue	Odour	Not available
Decomposition Temperature	Not available	Melting Point	Not available
Boiling Point	100°C (Water)	Solubility in Water	Completely miscible
Specific Gravity	1.3 kg/L	pH	Not available
Vapour Pressure	As for water	Vapour Density (Air=1)	Heavier than air
Evaporation Rate	Slower than butyl acetate	Odour Threshold	Not available
Viscosity	Not available	Partition Coefficient: n-octanol/water	Not available
Flash Point	Not applicable	Flammability	Non-combustible liquid.
Auto-Ignition Temperature	Not applicable	Flammable Limits - Lower	Not applicable
Flammable Limits - Upper	Not applicable		

10. STABILITY AND REACTIVITY

Chemical Stability

Stable under normal conditions of handling and storage.

Reactivity and Stability

Reacts with incompatible materials.

Conditions to Avoid

Extremes of temperature and direct sunlight. Protect from freezing.

Incompatible materials

Strong acids & oxidizing agents.

Hazardous Decomposition Products

Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon monoxide and carbon dioxide as well as trace amounts of vinyl acetate monomers, oxides of sulphur and oxides of nitrogen.

Possibility of hazardous reactions

Reacts with incompatible materials

Hazardous Polymerization

Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information

No toxicity data available for this material.

Ingestion

Ingestion of this product may irritate the gastric tract causing nausea and vomiting.

Inhalation

Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

Skin

May be irritating to skin. The symptoms may include redness, itching and swelling.

Eye

May be irritating to skin. The symptoms may include redness, itching and swelling.

Respiratory sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ cell mutagenicity

Not considered to be a mutagenic hazard.

Carcinogenicity

Suspected of causing cancer. Classified as a suspected human carcinogen.

Styrene is listed as a Group 2B: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

Reproductive Toxicity

Suspected of damaging fertility or the unborn child. Classified as a suspected human reproductive or developmental toxicant.

STOT-single exposure

Not expected to cause toxicity to a specific target organ.

STOT-repeated exposure

Not expected to cause toxicity to a specific target organ.

Aspiration Hazard

Not expected to be an aspiration hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicity

No ecological data available for this material.

Persistence and degradability

Not available

Mobility

Not available

Bioaccumulative Potential

Not available

Other Adverse Effects

Not available

Environmental Protection

Prevent this material entering waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal considerations**Product Disposal:**

Product wastes are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. This product can be disposed through a licensed commercial waste collection service. The product should be rendered non-hazardous before being sent to a licensed landfill facility.

Personal protective clothing and equipment as specified in Section 8 of this SDS must be worn during handling and disposal of this product. The ventilation requirements as specified in the same section must also be followed, and the precautions given in Section 7 of this SDS regarding handling must also be followed. Do not dispose directly into the sewerage system. Do not discharge into drains or watercourses or dispose where ground or surface waters may be affected.

In New Zealand, the disposal agency or contractor must comply with the New Zealand Hazardous Substances (Disposal) Regulations 2001. Further details regarding disposal can be obtained on the EPA New Zealand website under specific group standards.

Container Disposal:

The container or packaging must be cleaned and rendered incapable of holding any substance. It can then be disposed of in a manner consistent with that of the substance it contained. In this instance the packaging can be disposed through a commercial waste collection service.

Alternatively, the container or packaging can be recycled if the hazardous residues have been thoroughly cleaned or rendered non-hazardous.

In New Zealand, the packaging (that may or may not hold any residual substance) that is lawfully disposed of by householders or other consumers through a public or commercial waste collection service is a means of compliance with regulations.

14. TRANSPORT INFORMATION

Transport Information**Road and Rail Transport (ADG Code):**

Not classified as Dangerous Goods for transport according to the New Zealand Standard NZS 5433: 2012 Transport of Dangerous Goods on Land.

Marine Transport (IMO/IMDG):

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Air Transport (ICAO/IATA):

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

U.N. Number

None Allocated

UN proper shipping name

None Allocated

Transport hazard class(es)

None Allocated

Special Precautions for User

Not available

IMDG Marine pollutant

No

Transport in Bulk

Not available

15. REGULATORY INFORMATION

Regulatory information

Classified as Hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001, New Zealand.

Group Standard: Surface Coatings and Colourants (Toxic [6.7]) Group Standard 2006.

HSNO Approval Number

HSR002679

16. OTHER INFORMATION

Date of preparation or last revision of SDS

SDS Created: January 2017

References

- Standard for the Uniform Scheduling of Medicines and Poisons.
- Approved criteria for classifying hazardous substances [NOHSC:1008(2004)].
- National Code of Practice for the Preparation of Material Safety Data Sheets [NOHSC:2011(2003)].
- Australian Code for the Transport of Dangerous Goods by Road & Rail.
- Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
- Workplace exposure standards for airborne contaminants, Safe work Australia.
- American Conference of Industrial Hygienists (ACGIH)

Contact Person/Point

Chemist: Tel No: (08) 6272-3800

Emergency: Tel No: 0438 916 539

User Codes

User Title Label	User Codes
Rema Tip Top Product Code	B0292123D AU

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.