

# SAFETY DATA SHEET

## MONOCEL DECKING OIL

Infosafe No.: HXR48  
Version No.: 1.0  
ISSUED Date: 13/11/2014  
ISSUED BY BONDALL PTY LTD

### 1. IDENTIFICATION

---

**GHS Product Identifier**

MONOCEL DECKING OIL

**Product Code**

46805, 46806.

**Company Name**

BONDALL PTY LTD (ABN 27 008 734 996)

**Address**

113 Belmont Avenue  
Belmont  
WA 6104 Australia

**Telephone/Fax Number**

Tel: (08) 6272 3800

Fax: (08) 9277 4068

**Emergency phone number**

0400 705 773 or Poisons Information Centre: 13 11 26

**Recommended use of the chemical and restrictions on use**

A pigmented finish for timber decking. Applied by brush or roller.

### 2. HAZARD IDENTIFICATION

---

**GHS classification of the substance/mixture**

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

**Classification:**

Flammable Liquids: Category 3

Skin Corrosion/Irritation: Category 2

STOT Single Exposure Category 3 (narcotic)

STOT Repeated Exposure Category 1

Aspiration Hazard: Category 1

**Signal Word (s)**

DANGER

**Hazard Statement (s)**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

**Precautionary Statement (s)**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

**Pictogram (s)**

Flame, Health hazard, Exclamation mark

**Precautionary statement – Prevention**

P210 Keep away from heat/sparks/open flames/hot surfaces.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe fume/gas/mist/vapours/spray.

P264 Wash contaminated skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary statement – Response**

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P331 Do NOT induce vomiting.

P370+P378 In case of fire: Use carbon dioxide, dry chemical or foam for extinction. Alcohol resistant foam is preferred. If not available normal foam can be used.

P304+P340 IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P362 Take off contaminated clothing and wash before re-use.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P332+P313 If skin irritation occurs: Get medical advice/ attention.

**Precautionary statement – Storage**

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

#### Precautionary statement – Disposal

P501 Dispose of contents/container to an approved waste disposal plant.

#### Supplemental Information

The information under this heading is not mandatory under WHS Regulations. It is provided as information on other GHS hazard classes and categories and/or environmental hazards that are outside the scope of the WHS Regulations.

GHS classification: Hazardous to the Aquatic Environment - Long-Term Hazard: Category 2, Hazard statement: 411, Pictogram: Environment. Precautionary statement: P273, P391.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

---

#### Ingredients

Name	CAS	Proportion
Urethane resin	Proprietary	10-<30 %
White Spirit	64742-88-7	10-<30 %
Solvent naphtha, petroleum, light aromatic	64742-95-6	10-<30 %
Distillates, petroleum, straight run middle	64741-44-2	<10 %
Methyl ethyl ketoxime	96-29-7	<1 %
Ingredients determined not to be hazardous		To 100%

### 4. FIRST-AID MEASURES

---

#### Inhalation

If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

#### Ingestion

Do NOT induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.

#### Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

#### Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. If symptoms develop and/or persist seek medical attention.

**First Aid Facilities**

Eyewash, safety shower and normal washroom facilities.

**Advice to Doctor**

Treat symptomatically.

**Other Information**

For advice in an emergency, contact a Poisons Information Centre or a doctor at once. (131 126)

---

**5. FIRE-FIGHTING MEASURES**

---

**Suitable Extinguishing Media**

Use carbon dioxide, dry chemical or foam. Alcohol resistant foam is preferred. If not available normal foam can be used.

**Unsuitable Extinguishing Media**

Do not use water jet.

**Hazards from Combustion Products**

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

**Specific Hazards Arising From The Chemical**

Flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

**Hazchem Code**

•3Y

**Decomposition Temperature**

Not available

**Precautions in connection with Fire**

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

---

**6. ACCIDENTAL RELEASE MEASURES**

---

**Emergency Procedures**

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

## 7. HANDLING AND STORAGE

---

### Precautions for Safe Handling

Avoid contact with skin and eyes. Wear overalls, impervious gloves and safety glasses. Use in designated areas with local exhaust ventilation, away from sparks, flames and other ignition sources. Use approved flammable liquid storage containers in the work area. Prevent release of vapours and mists into workplace air. Keep containers tightly closed. Take precautionary measures against static discharges. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

### Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### Occupational exposure limit values

No exposure standards have been established for this material, however, the TWA exposure standards for refined mineral oil mist is 5 mg/m<sup>3</sup>. As with all chemicals, exposure should be kept to the lowest possible levels.

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

Source: Safe Work Australia

### Biological Limit Values

No biological limit allocated.

### Appropriate Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1: 2009 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

### Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/ mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any

necessary changes for individual circumstances.

### **Eye Protection**

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.

Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

### **Hand Protection**

Wear gloves of impervious material such as laminated film or nitrile. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

### **Body Protection**

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

---

### **Appearance**

Pale brownish liquid

### **Colour**

Pale brownish

### **Odour**

Hydrocarbon solvent odour

### **Decomposition Temperature**

Not available

### **Melting Point**

Not available

### **Boiling Point**

145°C - 200°C

### **Solubility in Water**

Insoluble

### **Specific Gravity**

0.900

### **pH**

Not available

### **Vapour Pressure**

0.7 kpa at 25°C

**Vapour Density (Air=1)**

>1

**Evaporation Rate**

<1 (n-Butyl acetate=1)

**Odour Threshold**

Not available

**Viscosity**

Not available

**Partition Coefficient: n-octanol/water**

Not available

**Flash Point**

33°C (Closed cup)

**Flammability**

Flammable liquid.

**Auto-Ignition Temperature**

Not available

**Flammable Limits - Lower**

0.9% v/v

**Flammable Limits - Upper**

5.5% v/v

**10. STABILITY AND REACTIVITY**

---

**Reactivity**

Refer to Sec 10: Possibility of hazardous reactions

**Reactivity and Stability**

Stable under normal conditions of storage and handling.

**Conditions to Avoid**

Heat, open flames and other sources of ignition.

**Incompatible materials**

Strong oxidising agents.

**Hazardous Decomposition Products**

Thermal decomposition may result in the release of toxic and/or irritating fumes, smoke and gases including: carbon dioxide and carbon monoxide.

**Hazardous Polymerization**

Will not occur.

## 11. TOXICOLOGICAL INFORMATION

---

### **Toxicology Information**

No toxicity data available for this material.

### **Ingestion**

May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may lead to death. May cause irritation to the mouth, throat, esophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.

### **Inhalation**

May cause irritation to the mucous membrane and upper airways, especially where vapours or mists are generated. Symptoms include sneezing, coughing, wheezing, shortness of breath, headache, dizziness, drowsiness nausea and vomiting.

### **Skin**

Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

### **Eye**

May be irritating to eyes. The symptoms may include redness, itching and tearing.

### **Respiratory sensitisation**

Not expected to be a respiratory sensitiser.

### **Skin Sensitisation**

Not expected to be a skin sensitiser.

### **Germ cell mutagenicity**

Not considered to be a mutagenic hazard.

### **Carcinogenicity**

Not considered to be a carcinogenic hazard.

### **Reproductive Toxicity**

Not considered to be toxic to reproduction.

### **STOT-single exposure**

May cause drowsiness or dizziness.

### **STOT-repeated exposure**

Causes damage to organs through prolonged or repeated exposure.

### **Aspiration Hazard**

May be fatal if swallowed and enters airways.



## 12. ECOLOGICAL INFORMATION

---

### **Ecotoxicity**

Toxic to aquatic life with long lasting effects.

### **Persistence and degradability**

Not available

### **Mobility**

Not available

### **Bioaccumulative Potential**

Not available

### **Environmental Protection**

Do not discharge this material into waterways, drains and sewers.

## 13. DISPOSAL CONSIDERATIONS

---

### **Disposal considerations**

Dispose of waste according to applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Advise flammable nature. Empty containers may contain flammable residues. Do not puncture, cut or weld on or near empty containers. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected.

## 14. TRANSPORT INFORMATION

---

### **Transport Information**

This material is a Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Class 3 - Flammable Liquids are incompatible in a placard load with any of the following:

- Class 1, Explosives
- Division 2.1, Flammable Gases, (Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500 L.)
- Division 2.3, Toxic Gases
- Division 4.2 Spontaneously Combustible Substances
- Division 5.1 Oxidising Agents and Division 5.2, Organic Peroxides
- Class 6 Toxic or Infectious Substances (where the flammable liquid is nitromethane)
- Class 7: Radioactive materials unless specifically exempted

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Class/Division: 3

UN No: 1263

Proper Shipping Name: PAINT (Solvent naphtha, petroleum, light aromatic) MARINE POLLUTANT

Packing Group: III

EMS: F-E,S-E

Special Provisions: 163 223 955

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Class/Division: 3

UN No: 1263

Proper Shipping Name: Paint

Packing Group: III

Packaging Instructions (passenger & cargo): 355

Packaging Instructions (cargo only): 366

Hazard Label: Flammable Liquid

Special Provisions: A3 A72

**U.N. Number**

1263

**UN proper shipping name**

PAINT

**Transport hazard class(es)**

3

**Packing Group**

III

**Hazchem Code**

•3Y

**EPG Number**

3C1

**IERG Number**

14

**IMDG Marine pollutant**

Yes

**15. REGULATORY INFORMATION**

---

**Regulatory information**

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

## Poisons Schedule

S5

## Australia (AICS)

All components of this product are listed on the Inventory or exempted.

## 16. OTHER INFORMATION

---

### Date of preparation or last revision of SDS

SDS Reviewed: November 2014

Supersedes: December 2009

### References

-Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice

-Standard for the Uniform Scheduling of Medicines and Poisons.

-Australian Code for the Transport of Dangerous Goods by Road & Rail.

-Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

-Workplace exposure standards for airborne contaminants, Safe work Australia.

-American Conference of Industrial Hygienists (ACGIH)

-Globally Harmonised System of classification and labelling of chemicals.

### Contact Person/Point

Chemist: Tel No: (08) 6272-3800

Emergency: Tel No: 0400 705 773

---

## END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of MSDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Chemical Safety International Pty Ltd.