# **SAFETY DATA SHEET**

# **MONOCEL FURNITURE OIL**

Infosafe No.: LQ07C ISSUED Date : 20/07/2016 ISSUED by: BONDALL PTY LTD

### 1. IDENTIFICATION

### **GHS Product Identifier**

MONOCEL FURNITURE OIL

#### **Product Code**

1L - 46812

#### **Company Name**

BONDALL PTY LTD (ABN 27 008 734 996)

#### Address

Australia: 113 Belmont Avenue Belmont, WA 6104 Australia

New Zealand: Owens Logistics,

3-5 Kahu Street,

Otahuhu, Auckland 2024

### Telephone/Fax Number

Tel: Australia: +61 (8)6272 3800 / New Zealand: 0800 474 7738

Fax: +61 (8)9277 4068

### **Emergency phone number**

AU: 1800 638 556, NZ: 0800 154 666

### Recommended use of the chemical and restrictions on use

Clear finish to preserve and maintain the natural look of outdoor timber furniture such as garden settings, BBQ trolleys and benches.

#### **Other Names**

Name	Product Code
MONOCEL FURNITURE OIL	500ml - 46811
MONOCEL FURNITURE OIL	500 ml trigger -46810

#### 2. HAZARD IDENTIFICATION

### GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) including Work, Health and Safety Regulations, Australia.

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Aspiration Hazard: Category 1 Flammable Liquids: Category 3

Hazardous to the Aquatic Environment - Long-Term Hazard: Category 2

Skin Corrosion/Irritation: Category 2 STOT Single Exposure: Category 3 (narcotic)

Signal Word (s) DANGER

# Hazard Statement (s)

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

### Pictogram (s)

Flame, Exclamation mark, Health hazard, Environment



#### Precautionary statement - Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash contaminated skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

#### Precautionary statement - Response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P331 Do NOT induce vomiting.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P370+P378 In case of fire: Use carbon dioxide, dry chemical or foam for extinction.

P391 Collect spillage.

#### Precautionary statement - Storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

#### Precautionary statement - Disposal

P501 Dispose of contents/container to an approved waste disposal plant.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Information on Composition

The classification as a carcinogen or mutagen does not apply since the substance contains less than 0.1% w/w benzene (EINECS no 200-753-7)

### Ingredients

Name	CAS	Proportion
Naphtha, petroleum, hydrodesulfurized heavy	64742-82-1	30-60 %
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	10-<30 %
Solvent naphtha (petroleum), light aromatic	64742-95-6	10-<30 %
Distillates, petroleum, straight run middle	64741-44-2	<10 %
Ingredients determined not to be hazardous		Balance

#### 4. FIRST-AID MEASURES

#### Inhalation

If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

#### Ingestion

Do NOT induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.

#### Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

#### **Eve contact**

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. If symptoms develop and/or persist seek medical attention.

#### **First Aid Facilities**

Eyewash, safety shower and normal washroom facilities.

#### **Advice to Doctor**

Treat symptomatically.

#### Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

#### 5. FIRE-FIGHTING MEASURES

#### **Suitable Extinguishing Media**

Use carbon dioxide, dry chemical or foam. Alcohol resistant foam is preferred. If not available normal foam can be used.

#### **Unsuitable Extinguishing Media**

Do not use water jet.

#### **Hazards from Combustion Products**

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

### **Specific Hazards Arising From The Chemical**

Flammable liquid and vapour. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

#### **Hazchem Code**

•3Y

#### **Decomposition Temperature**

Not available

#### Properties on Heating & in case of Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

### **6. ACCIDENTAL RELEASE MEASURES**

### **Emergency Procedures**

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

#### 7. HANDLING AND STORAGE

#### **Precautions for Safe Handling**

Avoid contact with skin and eyes. Wear overalls, impervious gloves and safety glasses. Use in designated areas with local exhaust ventilation, away from sparks, flames and other ignition sources. Use approved flammable liquid storage containers in the work area. Prevent release of vapours and mists into workplace air. Keep containers tightly closed. Take precautionary measures against static discharges. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

#### Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use, securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Occupational exposure limit values

No exposure standards have been established for this material. However, the available TWA exposure limits for Oil mist (refined mineral) is 5 mg/m<sup>3</sup>

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eighthour working day, for a five-day week.

#### **Biological Limit Values**

No biological limit allocated

### **Appropriate Engineering Controls**

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1:2009 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

### **Respiratory Protection**

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements. Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

#### **Eye Protection**

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

### **Hand Protection**

Wear gloves of impervious material. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations. Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

#### **Body Protection**

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### **Form**

Liquid

### **Appearance**

Clear liquid

#### Odour

Hydrocarbon solvent

### **Decomposition Temperature**

Not available

### **Melting Point**

Not available

### **Boiling Point**

Not available

### **Solubility in Water**

Insoluble

#### **Specific Gravity**

0.86

# рΗ

Not applicable

### **Vapour Pressure**

Not available

### Vapour Density (Air=1)

Not available

### **Evaporation Rate**

Not available

### **Odour Threshold**

Not available

### Viscosity

Not available

#### Partition Coefficient: n-octanol/water

Not available

### **Flash Point**

Not available

#### **Flammability**

Flammable

### **Auto-Ignition Temperature**

Not available

# Flammable Limits - Lower

Not available

### Flammable Limits - Upper

Not available

# **10. STABILITY AND REACTIVITY**

### Reactivity

Reacts with incompatible materials.

### **Chemical Stability**

Stable under normal conditions of storage and handling.

#### **Conditions to Avoid**

Heat, sparks, open flames and other ignition sources.

#### Incompatible materials

Strong oxidising agents.

#### **Hazardous Decomposition Products**

Thermal decomposition may result in the release of toxic and/or irritating fumes, smoke and gases including: carbon monoxide and carbon dioxide.

#### Possibility of hazardous reactions

Not available

### **Hazardous Polymerization**

Will not occur

#### 11. TOXICOLOGICAL INFORMATION

#### **Toxicology Information**

No toxicity data available for this material.

#### Ingestion

May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may lead to death. May cause irritation to the mouth, throat, esophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.

#### **Inhalation**

May cause irritation to the mucous membrane and upper airways, especially where vapours or mists are generated. Symptoms include sneezing, coughing, wheezing, shortness of breath, headache, dizziness, drowsiness, nausea and vomiting.

#### Skin

Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

#### Eye

May be irritating to eyes. The symptoms may include redness, itching and tearing.

### **Respiratory sensitisation**

Not expected to be a respiratory sensitiser.

#### **Skin Sensitisation**

Not expected to be a skin sensitiser.

#### Germ cell mutagenicity

Not considered to be a mutagenic hazard.

#### Carcinogenicity

Not considered to be a carcinogenic hazard.

Mineral oils, highly-refined is listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

#### **Reproductive Toxicity**

Not considered to be toxic to reproduction.

#### STOT-single exposure

May cause drowsiness or dizziness.

### STOT-repeated exposure

Not expected to cause toxicity to a specific target organ.

### **Aspiration Hazard**

May be fatal if swallowed and enters airways.

### 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

Toxic to aquatic life with long lasting effects.

#### Persistence and degradability

Not available

#### Mobility

Not available

#### **Bioaccumulative Potential**

Not available

#### **Other Adverse Effects**

Oil spills can smother and suffocate aquatic life by preventing passage of oxygen into water. Oil contamination can also foul and smother birds and marine animals.

#### **Environmental Protection**

Do not discharge this material into waterways, drains and sewers.

#### 13. DISPOSAL CONSIDERATIONS

### **Disposal considerations**

Dispose of waste according to applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Advise flammable nature. Empty containers may contain flammable residues. Do not cut, puncture or weld on or near containers. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected.

#### 14. TRANSPORT INFORMATION

#### **Transport Information**

Road and Rail Transport (ADG Code):

This material is a Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Class 3 - Flammable Liquids are incompatible in a placard load with any of the following:

- Class 1, Explosives
- Division 2.1, Flammable Gases, (Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500 L.)
- Division 2.3, Toxic Gases
- Division 4.2 Spontaneously Combustible Substances
- Division 5.1 Oxidising Agents and Division 5.2, Organic Peroxides
- Class 6 Toxic or Infectious Substances (where the flammable liquid is nitromethane)
- Class 7: Radioactive materials unless specifically exempted

#### Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Class/Division: 3 UN No: 1263

Proper Shipping Name: PAINT (Petroleum hydrocarbons MARINE POLLUTANT)

Packing Group: III EMS: F-E, S-E

Special Provisions: 163, 223, 367, 955

### Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 1263

**Proper Shipping Name: PAINT** 

Class: 3

Packing Group: III

Packaging Instructions (passenger & cargo): 355 Packaging Instructions (cargo only): 366

Hazard Label: Flammable liquid Special provisions: A3, A72, A192

**U.N. Number** 

1263

**UN proper shipping name** 

**PAINT** 

Transport hazard class(es)

**Packing Group** 

**Hazchem Code** 

• 3Y

**IERG Number** 

14

**IMDG Marine pollutant** 

**Transport in Bulk** 

Not available

**Special Precautions for User** 

Not available

#### 15. REGULATORY INFORMATION

#### **Regulatory information**

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

#### **Poisons Schedule**

**S**5

#### 16. OTHER INFORMATION

### Date of preparation or last revision of SDS

SDS Reviewed: July 2016 Supersedes: June 2011

#### References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH.

Globally Harmonised System of classification and labelling of chemicals.

### **Contact Person/Point**

Chemist: Tel No: (08) 6272-3800 Emergency: Tel No: 0438 916 539

### **END OF SDS**

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence o	or for
inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.	