



Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066

bondall@bondall.com
www.bondall.com

MONOCEL ALL PURPOSE TIMBER SEALER

REVISED: AUGUST 2003

DESCRIPTION

Bondall Monocel All Purpose Timber Sealer is a revolutionary penetrating 100% acrylic sealer. It will seal, bind, protect and is a water repellent for most timber surfaces. It is designed for subsequent topcoating and is not intended as a permanent coating. Once a surface has been treated with All Purpose Timber Sealer it can be coated with Bondall's Timber Care Range.

This product is intended for application onto untreated timber. The penetrating properties of the product make it ideal for sealing timber surfaces such as doors, cladding, railings, skirting boards, windows and MDF boards.

TEST AREA: Always test on a small inconspicuous area, to ensure that the product is achieving the desired result, prior to application over the entire area.

FEATURES AND BENEFITS

- Easy to use
- Quick recoating time
- Water clean up

SURFACE PREPARATION

- Surface preparation is important. All surfaces to be coated with All Purpose Timber Sealer should be clean and dry, free from wax, oil, grease and other contaminants.
- New dressed timber should be fine sanded and then thoroughly dusted prior to application of the sealer coat, this includes filling any holes. It may be necessary to wipe the surface down with a mild sugar soap solution prior to coating it.

APPLICATION

- Stir well before and during use. DO NOT SHAKE the contents as shaking will produce bubbles, which may become trapped on the surface.
- Apply first coat direct from the container by brush, roller or spray. Allow to dry for 30 minutes before applying a second coat.
- Allow 1-3 hours drying before top coating.
- Apply each coat neat and evenly. Proper penetration of the first coat is very important.
- Should only one coat be applied check for beading of water to indicate the coating is effective.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066
bondall@bondall.com
www.bondall.com

COVERAGE

Approximately 10-12 square metres per litre on hard timber and 8-10 square metres per litre on soft timber. Coverage rates are dependant on surface porosity, texture and application technique used.

THINNING

If required use water. Do not thin down by more than 5% by volume.

GLOSS LEVEL

Not applicable.

DRYING TIME

- All Purpose Timber Sealer is touch dry in approximately 30 minutes at 25°C but should be left for 1-3 hours before top coating.
 - Drying times are a guide only. Longer drying times may be required under cooler or humid conditions.
 - Do not apply if temperature is below 10°C or if rain is expected with 24 hours.
- Ensure adequate ventilation during use.

CLEAN UP

Clean all equipment promptly with warm water and a little detergent followed by a fresh water rinse immediately after use.

COLOUR

Clear

SIZES

1 Litre and 4 Litre



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066
bondall@bondall.com
www.bondall.com

PRECAUTION/FIRST AID

It is recommended that normal personal protective clothing should be worn, including coveralls, impervious gloves and goggles. Avoid unnecessary skin contact and inhalation. Provide adequate ventilation. If swallowed, contact a doctor or the Poison Information Centre on 13 11 26. Give a glass of water to drink and do not induce vomiting.

DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions makes it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Service on 1800 810 123 or (08) 9277 6844



Wholly Australian Owned & Manufactured

the solution  bondall

