

POT SEALER

CC0010 REVISED APRIL 2003

DESCRIPTION

Bondall Pot Sealer is the ideal choice for sealing unglazed pots. It will seal bind and protect most pot surface while still retaining a clear natural look. Bondall Pot Sealer reduces staining and soiling, resists algal and fungal growth and offers outstanding exterior durability.

Note: This product is not designed to be used as a waterproofer for a water holding vessel e.g. a pot to be used as a pond for fish etc and it is not suitable for use on glazed surfaces.

TEST AREA: Always test on a small inconspicuous area to ensure that the product achieves the desired result prior to application over the entire area.

FEATURES AND BENEFITS

- · Seals, binds and protects most pots.
- Gives a clear natural look.
- Easy to use.
- · Water based.

SURFACE PREPARATION

Proper penetration of the first coat is very important. Surfaces should be thoroughly cleaned as any stains present will become more apparent once sealed. Soiling, grease and oil stains can be removed using Bondall's environmentally friendly Pot & Ornament Cleaner. Bore and rust stains, efflorescence stains and moss and mould also should be treated prior to sealing. Please refer to the Bondall range of appropriate cleaners to prepare the surface.

APPLICATION

Shake the container gently before use. Hold nozzle approximately 300mm from surface. Apply the first coat neatly and evenly and allow a minimum of 4 hours between coats. At least two coats must be applied. If running occurs, wipe down with a damp cloth. Care should be taken to apply evenly and not too heavily on pitted surfaces.

COVERAGE

This bottle will cover approximately 4 square metres depending on the porosity of the surface it is being applied to..







bondali@bondal.com



THINNING

Not required - ready to use.

GLOSS LEVEL

Low sheen finish but could increase from substrate to substrate.

Over application will result in the surface becoming glossy or a milky film may occur from trapped moisture. May darken some surfaces.

DRYING TIME

May be recoated in no less than 4 hours at 25° C.

Allow to dry for at least 48 hours before filling with soil etc.

Drying times are a guide only. Longer drying times may be required under cooler or humid conditions.

CLEAN UP

DO NOT POUR CONTENTS OR WASHING DOWN DRAINS OR SINKS.

Clean equipment and spills with water and mild detergent

COLOUR

Appears white in container but dries clear.

SIZES

1 Litre and 4 Litre

PRECAUTION/FIRST AID

Avoid contact with skin and eyes. Should contact occur to the eyes flush with water for 15 minutes and seek medical attention should irritation develop. It is recommended that normal personal protective clothing should be worn, including coveralls, impervious gloves and goggles. Avoid unnecessary skin contact and inhalation – use a suitable respirator if spray application is employed. If swallowed, contact a doctor or the Poison Information Centre on 13 11 26. Give water to drink and do not induce vomiting.









113 Belmont Ave Belmont WA 6104

PO Box 111

P: 08 9277 6844 F: 08 9277 4068

bondali@bondali.com www.bondali.com



The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions makes it impossible for the company to assume liability for anyloss, consequential or otherwise, arising from the use of this product. Should the product befound defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Service on 1800 810 123 or (08) 9277 6844





