

SAFETY DATA SHEET

POT & ORNAMENTAL SEALER

Infosafe No.: HXR65
Version No.: 1.0
ISSUED Date: 12/12/2014
ISSUED BY BONDALL PTY LTD

1. IDENTIFICATION

GHS Product Identifier

POT & ORNAMENTAL SEALER

Product Code

94033, 94035.

Company Name

BONDALL PTY LTD (ABN 27 008 734 996)

Address

113 Belmont Avenue
Belmont
WA 6104 Australia

Telephone/Fax Number

Tel: (08) 6272 3800
Fax: (08) 9277 4068

Emergency phone number

0400 705 773 or Poisons Information Centre: 13 11 26

Recommended use of the chemical and restrictions on use

To provide a waterproof, clear exterior coating for: concrete; stone; brick; clay tile; rammed earth or low porosity substrates.

2. HAZARD IDENTIFICATION

GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia
Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Classification:

Eye Damage/Irritation: Category 2A

Signal Word (s)

WARNING

Hazard Statement (s)

H319 Causes serious eye irritation.

Pictogram (s)

Exclamation mark

**Precautionary statement – Prevention**

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement – Response

EYE

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

Supplemental Information

The information under this heading is not mandatory under WHS Regulations. It is provided as information on other GHS hazard classes and categories and/or environmental hazards that are outside the scope of the WHS Regulations.

GHS classification: Skin Corrosion/Irritation: Category 3. Hazard statement: H316. Precautionary statement: P332+313.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients

Name	CAS	Proportion
Acrylic polymer	Proprietary	10-<30 %
2-Butoxyethanol	111-76-2	<10 %
2-(2-Butoxyethoxy) ethanol	112-34-5	<10 %
Terbutryn	886-50-0	<0.1 %
2-n-Octyl-4-isothiazolin-3-one	26530-20-1	<0.05 %
1,2-Benzisothiazolin-3-one	2634-33-5	<0.05 %
2-Methyl-2H-isothiazolin-3-one	2682-20-4	<0.01 %
Other ingredients determined not to be hazardous, including water.		Balance

4. FIRST-AID MEASURES

Inhalation

If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.

Ingestion

Do not induce vomiting. Wash out mouth thoroughly with water. Seek medical attention.

Skin

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

Eye contact

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

First Aid Facilities

Eye wash and normal washroom facilities.

Advice to Doctor

Treat symptomatically.

Other Information

For advice in an emergency, contact a Poisons Information Centre (Phone 13 11 26 in Australia) or a doctor.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray, water fog, foam, carbon dioxide and dry chemical powder.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide and carbon dioxide as well as trace amounts of acrylic monomers, oxides of sulphur and oxides of nitrogen.

Specific Hazards Arising From The Chemical

This product is non combustible. However, following evaporation of aqueous component under fire conditions, the non-aqueous component may decompose and/or burn.

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) and full protective clothing to prevent exposure to vapours, fumes and products of combustion. Water spray may be used to cool down heat-exposed containers.

6. ACCIDENTAL RELEASE MEASURES

Emergency Procedures

Wear appropriate personal protective equipment and clothing to prevent exposure. Increase ventilation. If possible contain the spill. Place inert absorbent material onto spillage. Collect the material and place into a suitable labelled container. Do not dilute material but contain. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Avoid inhalation of vapours and mists, and skin or eye contact. Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Maintain high standards of personal hygiene i.e. Washing hands prior to eating, drinking, smoking or using toilet facilities.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated area, out of direct sunlight. Store in suitable, labelled containers. Keep containers tightly closed. Store away from incompatible materials. Ensure that storage conditions comply with applicable local and national regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limit values

No exposure value assigned for this material by Safe Work, Australia. However, the available exposure limits for ingredients are listed below:

Safe Work, Australia Exposure Standards:

2-(2-Butoxyethoxy) ethanol:

TWA: 20 ppm

TWA: 96.9 mg/m³

STEL: 50 ppm

STEL: 242 mg/m³

NOTICES: Sk

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

'Sk' Notice: Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

Biological Limit Values

Name: 2-butoxyethanol

Determinant: Butoxyacetic acid (BAA) in urine*

Value: 200mg/g creatinine

Sampling time: end of shift.

*with hydrolysis

Source: American Conference of Industrial Hygienists (ACGIH)

Appropriate Engineering Controls

Use with good general ventilation. If mists or vapours are produced, local exhaust ventilation should be used. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable organic vapor/ mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.

Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Hand Protection

Wear gloves of impervious material such as laminated film or nitrile. Avoid gloves made of natural latex. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Body Protection

Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Milky white, free flowing liquid; dries clear.

Odour

Mild acrylic odour.

Decomposition Temperature

Not available

Melting Point

0°C (Water)

Boiling Point

100°C (Water)

Solubility in Water

Miscible in all proportions.

Solubility in Organic Solvents

Not available

Specific Gravity

1.0

pH

Slightly alkaline

Vapour Pressure

17 mmHg (20°C)

Vapour Density (Air=1)

Not available

Evaporation Rate

Not available

Viscosity

10 cP (25°C)

Volatile Component

Organic Volatiles: <1% w/w

Partition Coefficient: n-octanol/water

Not available

Flash Point

Not applicable

Flammability

Non-combustible liquid.

Auto-Ignition Temperature

Not available

Flammable Limits - Lower

Not applicable

Flammable Limits - Upper

Not applicable

10. STABILITY AND REACTIVITY

Reactivity

Refer to Sec 10: Possibility of hazardous reactions.

Chemical Stability

Stable under normal conditions of storage and handling.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible materials

Oxidising agents and strong acids.

Hazardous Decomposition Products

Thermal decomposition may result in the release of toxic and/or irritating fumes including carbon monoxide and carbon dioxide as well as trace amounts of acrylic monomers, oxides of sulphur and oxides of nitrogen.

Possibility of hazardous reactions

Reacts with incompatible materials.

Hazardous Polymerization

Will not occur.

11. TOXICOLOGICAL INFORMATION

Toxicology Information

No toxicity data available for this material.

Ingestion

Ingestion of this product may irritate the gastric tract causing nausea and vomiting.

Inhalation

Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

Skin

Causes mild skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

Eye

Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

Respiratory sensitisation

Not expected to be a respiratory sensitiser.

Skin Sensitisation

Not expected to be a skin sensitiser.

Germ cell mutagenicity

Not considered to be a mutagenic hazard.

Carcinogenicity

Not considered to be a carcinogenic hazard.

2-Butoxyethanol is listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

Reproductive Toxicity

Not considered to be toxic to reproduction.

STOT-single exposure

Not expected to cause toxicity to a specific target organ.

STOT-repeated exposure

Not expected to cause toxicity to a specific target organ.

Aspiration Hazard

Not expected to be an aspiration hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicity

No ecological data available for this material.

Persistence and degradability

Not available

Mobility

Not available

Bioaccumulative Potential

Not available

Environmental Protection

Prevent this material entering waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Disposal considerations

The disposal of the spilled or waste material must be done in accordance with applicable local and national regulations.

14. TRANSPORT INFORMATION

Transport Information

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

U.N. Number

None Allocated

UN proper shipping name

None Allocated

Transport hazard class(es)

None Allocated

IMDG Marine pollutant

No

15. REGULATORY INFORMATION

Regulatory information

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

Classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP)

Poisons Schedule

S5

Australia (AICS)

All components of this product are listed on the Inventory or exempted.

16. OTHER INFORMATION

Date of preparation or last revision of SDS

SDS Reviewed: December 2014

Supersedes: August 2006, February 2010

References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice
Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants, Safe work Australia.

American Conference of Industrial Hygienists (ACGIH)

Globally Harmonised System of classification and labelling of chemicals.

Contact Person/Point

Chemist: Tel No: (08) 6272-3800

Emergency: Tel No: 0400 705 773

User Codes

User Title Label	User Codes
Field 4	328560

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of MSDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Chemical Safety International Pty Ltd.