



Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066

bondall@bondall.com
www.bondall.com

THOMPSON'S WATER SEAL ULTRA

DESCRIPTION

Thompson's Water Seal Ultra is a unique, one coat application, high performance, transparent water repellent, designed to penetrate exterior brick and stonework, to provide a barrier against rain damage.

SURFACE PREPARATION AND APPLICATION

Thompson's Water Seal Ultra is recommended for use on all types of exterior brickwork and stone, which is above ground level and free from cracks exceeding 0.15 mm width.

APPLICATION PROCEDURE Thompson's Water Seal Ultra should be applied to clean surfaces which are free from moulds, fungal coatings and all other coatings which may interfere with the penetration of Thompson's Water Seal Ultra. Remove moulds and fungal growths by brushing with a stiff bristle brush. Eradicate any fungal or mould growth by treating affected areas with dilute household bleach solution (1 part bleach to 4 parts water) preferable applied in dry weather. Leave for 48 hours and rinse area thoroughly with water, and allow to dry.

Thompson's Water Seal Ultra is not recommended for use over painted areas. Carry out any repairs and fill any surface cracks prior to treatment. Thompson's Water Seal Ultra can be applied to dry and damp (but not saturated) areas. Ensure that the whole wall is treated, not just isolated areas. Application Shake the can vigorously before use. Apply using brush or roller in one continuous operation. On vertical surfaces, working from the bottom up, divide the area into approximately 1 metre sections. Each section should then be fully saturated. Best results are achieved by brushing/rolling in all directions, paying particular attention to mortar lines. Rework the section to ensure complete saturation. Finish each section before moving onto the next. On horizontal surfaces saturate well. After 15 minutes remove puddles by redistributing to dry areas. Use at full strength. Do not dilute.

COVERAGE

Thompson's Water Seal Ultra will cover approximately 4 m²/litre. Coverage will vary depending on the texture and porosity of the surface to be treated.

THINNING

Not recommended

GLOSS LEVEL

Not applicable.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066
bondall@bondall.com
www.bondall.com

DRYING TIME

Thompson's Water Seal Ultra is touch dry in approximately 2 hours. Drying time will vary depending on the absorbency of the surface, temperature and relative humidity.

CLEAN UP

Remove as much product as possible from equipment before washing. All equipment should be cleaned immediately after use with detergent and water.

DISPOSAL Some local authorities have special facilities for the disposal or dispensing of waste coatings. Do not empty product into drains or watercourses.

COLOUR

Milky- Clear when applied

SIZES

1 Litre and 4 Litre

PRECAUTION/FIRST AID

Observe and follow all warnings and instructions for use shown on the pack. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Ensure good ventilation when applying and during drying. Keep out of reach of children. Specific health and safety data sheets are available on request.

FLAMMABILITY Flash point above 61°C. Non-flammable product.

DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions makes it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Service on 1800 810 123 or (08) 9277 6844



Wholly Australian Owned & Manufactured

the solution  bondall

