



Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066
bondall@bondall.com
www.bondall.com

WATER BASED BITUMINOUS MEMBRANE

REVISED: SEPTEMBER 2006

DESCRIPTION

Bondall Water Based Bituminous Membrane is a general purpose coating for water proofing and protecting surfaces. It is reinforced with rubber latex to provide flexibility and increased strength.

Bondall Water Based Bituminous Membrane can be used for retaining walls, planter boxes, roofs, gutters and down pipes and in most instances where water proofing is required from the positive side. This product is safe for contact with drinking water and is suitable for immersed situations e.g. ponds, water features etc.

FEATURES AND BENEFITS

- Easy to use
- Safe for drinking water
- Non-carcinogenic
- Flexible
- Non-flammable
- Excellent adhesion
- Quick drying

SURFACE PREPARATION

- Surface preparation is critical. Ensure all surfaces to be coated are clean, dry and free from dust laitance and other contaminants and in a sound condition.
- Corroded metals should be wire brushed and treated with an anti-corrosive primer.
- When repairing areas with small holes or cracks or when joint movement is likely, reinforce these areas using Bondall Poly Weave. Apply a priming coat and work Bondall Poly Weave into Bondall Water Based Bituminous Membrane using a roller or brush. Allow to dry completely.
- Bondall Water Based Bituminous Membrane must always be applied to the positive side (i.e. to prevent moisture entering the substrate).

APPLICATION

- Stir well before use.
- Bondall Water Based Bituminous Membrane can be applied by brush or roller.
- Apply in even coats, referring to the coverage rates. Do not attempt to achieve high film thickness in one coat.
- Apply the second coat at right angles (90°) to the first coat.
- When used, ensure Bondall Poly Weave is covered completely.
- A minimum of 2 coats must be applied.

COVERAGE

1.5m² per litre

We recommend a minimum of 2 coats. In some cases depending on the type of substrates or uneven surfaces, 3 coats may be required.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104

PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066

bondall@bondall.com
www.bondall.com

THINNING

Not recommended

GLOSS LEVEL

Not applicable.

DRYING TIME

Bondall Water Based Bituminous Membrane may be recoated after 30 minutes. Do not backfill until after 7 days.
Do not apply when temperature is below 10°C or relative humidity is above 80% or when rain is expected within 24 hours.

CLEAN UP

Clean all equipment promptly with mineral turps, followed by warm water with a little detergent and a fresh water rinse immediately after use. Do not pour contents or washings down drains or sinks. Dispose as per your local council regulations.

COLOUR

Black

SIZES

1 Litre and 4 Litre

PRECAUTION/FIRST AID

It is recommended that normal personal protective clothing should be worn, including coveralls, impervious gloves and goggles. Avoid unnecessary skin contact. Use a suitable respirator if spray application is employed. If swallowed, contact a doctor or the Poison Information Centre on 13 11 26. Give a glass water to drink and do not induce vomiting. A Material Safety Data Sheet is available on request.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD
ACN: 008 734 096
ARS: 27 008 734 096

113 Belmont Ave
Belmont WA 6104
PO Box 111
Cloverdale WA 6985

P: 08 9277 6844
F: 08 9277 4066
bondall@bondall.com
www.bondall.com


DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions makes it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Service on 1800 810 123 or (08) 9277 6844



Wholly Australian Owned & Manufactured

the solution  bondall

