



Bondall PTY LTD  
ACN: 008 734 096  
ARS: 27 008 734 096

113 Belmont Ave  
Belmont WA 6104

PO Box 111  
Cloverdale WA 6985

P: 08 9277 6844  
F: 08 9277 4066

bondall@bondall.com  
www.bondall.com

## PONDITITE CLEAR

REVISED: FEBRUARY 2005

### DESCRIPTION

Bondall PondTite Clear is a brushable product that forms a tough, seamless, waterproof coating for water bearing objects. It is suitable for use on masonry surfaces only. It is environmentally friendly, simple to use and easily washable/cleanable

Bondall PondTite Clear (unlike the PondTite colour range) is a non-flexible product that will not allow for any surface movement. When using PondTite Clear, it is therefore essential that the surface area is of high quality. If the surface is questionable, PondTite Clear is not suitable for use and a PondTite colour-based product is recommended as an alternative.

### FEATURES AND BENEFITS

√ Ideal for:

Fish ponds

Fountains

Bird Baths

Water features

Holding tanks (non-potable)

Reflective pools

X Not intended for:

Swimming Pools

Spas

Glass or fiberglass

Glazed or semi-glazed surfaces

Plastic, metal, wood

Painted surfaces

### SURFACE PREPARATION

- Carefully prepare the surface area.
- Ensure surface is free from any sharp edges or 'dags'.
- Ensure there is no presence of renewable moisture.
- Fill any holes or cracks with a fine sand/cement mortar (Hydrocrete recommended), thoroughly worked into the area.
- Clean thoroughly to ensure surface is free from dirt, dust, salts, grease, oil or other contaminants.
- If uncertain of surface preparation requirements, surface conditions or suitability of product, please refer to special instructions on Bondall's website [www.bondall.com](http://www.bondall.com) or contact the Bondall Advisory Service on Toll Free 1800 810 123 or (08) 9277 6844.

### APPLICATION

- Do not apply if temperature is below 10°C, if humidity is high or if rain is expected.
- Stir PondTite Clear slowly with broad blade or paddle. Do not shake tin.
- Use a medium to firm bristle, quality paintbrush.
- Apply directly from tin as dilution is generally not necessary. In warm conditions, to aid application, dilute by no more than 5% using clean water.
- Avoid excess build-up in corners ensuring no bubbles are left.
- Allow first coat to dry overnight or longer if conditions are cold, damp or humid.
- Apply second coat at right angles to first coat.
- Allow at least 7 days drying time before filling with water.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD  
ACN: 008 734 096  
ARS: 27 008 734 096

113 Belmont Ave  
Belmont WA 6104  
PO Box 111  
Cloverdale WA 6985

P: 08 9277 6844  
F: 08 9277 4066  
bondall@bondall.com  
www.bondall.com

## COVERAGE

- Approximately 10 square metres per Litre, depending on the texture and porosity of the surface.

## FILLING OF POND

- Mix small amount of dishwashing liquid with clean water in a bucket.
- Sponge surface with soapy water to remove any PondTite Clear residue.
- Rinse pond thoroughly with fresh, clean water, removing all traces of detergent.
- Fill pond with clean water and leave for 1-2 days.
- Empty pond and refill with clean water again.
- Before adding fish or plants, carefully follow water conditioning instructions from fish or aquaculture supplier.

## CLEAN UP

- Clean all equipment promptly with soapy water and a stiff bristle or wire brush.
- Use methylated spirits if product has dried or hardened.
- Rinse thoroughly with fresh water.
- Please dispose of any waste materials responsibly.
- Do not put PondTite Clear or washings down drains or sinks.

## COLOUR

Clear

## SIZES

Available in 1 Litre, 4 Litre and 15 Litre.

## PRECAUTION/FIRST AID

- Avoid contact with eyes or skin.
- Wear protective gloves, clothing and eyewear (recommended).
- Seal container when not in use.
- Keep out of reach of children.
- If accidental poisoning occurs, seek urgent medical advice or contact Poisons Information Centre on 13 11 26.



Wholly Australian Owned & Manufactured

the solution  bondall





Bondall PTY LTD  
ACN: 008 734 096  
ARS: 27 008 734 096

113 Belmont Ave  
Belmont WA 6104

PO Box 111  
Cloverdale WA 6985

P: 08 9277 6844  
F: 08 9277 4066

bondall@bondall.com  
www.bondall.com

## DISCLAIMER

The information contained here is given in good faith and is intended to be of assistance to users. The performance of this product is dependant upon its correct preparation, application onto a sound surface and attention to the instructions on the label. The wide variety of surface conditions make it impossible for the company to assume liability for any loss, consequential or otherwise, arising from the use of this product. Should the product be found defective our liability shall be limited to the replacement of the product only. We reserve the right to amend specifications and application techniques without prior notice.

For further advice please contact the Bondall Building and Renovating Advisory Service on 1800 810 123 or (08) 9277 6844.

## SPECIAL INSTRUCTIONS

Before using Bondall PondTite Clear, please follow these special instructions to ensure the surface area is prepared correctly. All other instructions are clearly outlined on the product label and must be carefully followed. The overall performance of this product relies on the correct preparation, application to high quality surfaces only and adherence to the instructions provided.

### New concrete surfaces

(e.g. sand/cement renders, concrete blocks, limestone, sandstone, bricks, fibre cement sheeting)

- Allow 1 week curing for every 25mm of concrete.
- Clean thoroughly to remove any laitance, which may effect the adhesion of PondTite Clear

### Existing / mature masonry surfaces

- Remove any algal or fungal growth with Bondall Moss & Mould Eliminator.

### Previously coated or painted surfaces

- Completely remove previous coatings right back to the original surface layer.

### Moisture Test

- Prior to application of product please test surface for evidence of moisture. Cover surface with a small black plastic sheet and tape it down. Leave it in place for 24hrs before removing tape to check if any moisture is present on the underneath of the black plastic sheet. Presence of moisture will indicate rising damp, in such instance the preferred product for application will be the usage of Bondall's PondTite colour range in conjunction with Bondall's Epoxy Prep.

### Stonework

- Bed in sand / cement mortar (Bondcrete recommended).

For questions or advice about the application of PondTite, please contact:

Bondall Advisory Service

Toll Free 1800 810 123

or (08) 9277 6844



Wholly Australian Owned & Manufactured

the solution  bondall

